


PINOLITE Batten (Integrated)



Class II	IK03	IP20
----------	------	------



Product Code:

FIB71600v0

Electrical Data	
Voltage (V)	220-240V
Product Data	
Product Wattage (W)	19
Beam Angle (°)	120
Colour Temperature (K)	Warmwhite (3000K), Coolwhite (4000K), Daylight (6500K)
Colour Render Index (Ra)	> Ra80
Colour	White (WH13)
Materials	Polycarbonate
Protection Class	Class II
Dimmable	No
Operating Temperature	-30°C to +40°C
Application	Office, Display Shelves, Light Troughs, Shops and Boutiques, Wall Lighting
Performance Data	
Luminous Flux (lm)	1600 [3000K], 1700 [4000K], 1700 [6500K]
Luminous Efficacy (lm/W)	84 [3000K], 89 [4000K], 89 [6500K]
Rated Life (hrs)	35000 hrs at L70 B50 at Ta 25°C
IP Rating	IP20
Product Dimensions	
Length (mm)	880
Width (mm)	23
Height (mm)	39
Remarks: Accessories: LA8002 1.8m Power Cord LA8036 150mm Patch Cord LA8004 Angle Joint for PINOLITE LA8005 Mounting Clips (Comes with the MEGAMAN® PINO) LA8039 Female Pole Protective Cap	

Product Code: FIB71600v0

MEGAMAN® 2005-2020. All Rights Reserved.

This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.cn.megaman.cc