



DINO 2 Waterproof Batten (Integrated) - Clear Prismatic Diffuser Options



Integrated LED Luminaire
FOB61100v1-pl

Product Code:

FOB61100v1-pl

Electrical Data	
Voltage (V)	220-240V
Power Factor (λ)	> 0.9
Product Data	
Product Wattage (W)	63
Beam Angle (°)	160
Colour Temperature (K)	Warmwhite (3000K), Coolwhite (4000K)
Colour Render Index (Ra)	Ra80
Colour	Silver (SV16)
Materials	Polycarbonate with clear prismatic diffuser
Protection Class	Class II
Dimmable	No
Operating Temperature	-30°C to +40°C
Weight (g)	1645
Application	Car parks, Underground Areas, Warehouses, Workshops
Performance Data	
Luminous Flux (lm)	6300 [3000K], 6500 [4000K]
Luminous Efficacy (lm/W)	100 [3000K], 103 [4000K]
Rated Life (hrs)	50000
IP Rating	IP66
Product Dimensions	
Length (mm)	1572
Width (mm)	62
Height (mm)	56

Product Code: FOB61100v1-pl

MEGAMAN® 2005-2020. All Rights Reserved.

This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.cn.megaman.cc